DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D500-572 REV. A OR LATER APPROVED REVISION AND INSTALLATION FOR CONTINUED AIRWORTHINESS ICA-D500-572 REV. 0 OR LATER APPROVED REVISIONS

REF. TCCA STC: SH90-17 REF. FAA STC: SH849NE REF. JAA STC: ACG.21NE2.104

### 1.0 INTRODUCTION

It has come to DART's attention that the D2438 Clamps provided with D500-572-011 Bearpaw Kit at CHG 005 and earlier and D500-572-021 Bearpaw kit at CHG 006 and earlier might be too long.

## 2.0 PURPOSE

The purpose of this DSI (DART Service Instruction) is to change the clamp configuration for D500-572-011 Bearpaw Kits at CHG 006 and later and D500-572-021 Bearpaw Kits at CHG 007 and later and to introduce the DSI 9770-011 Clamp Kit for operators who wish to upgrade their existing D500-572-011/-021 Bearpaw Kits in service.

## 3.0 INSTRUCTIONS

These instructions reference Figure 1 of this service instruction. Figure 1 replaces Sections A-A and B-B of IIN-D500-572 (ref. Figures 2 and 3) and ICA-D500-572 (ref. Figures 32-1 and 32-2).

- 3.1 Jack up the aircraft and ensure the skidtubes are serviceable.
- 3.2 (i) For the D500-572-011 Bearpaw Installation: Position D2435 Bearpaw on the aft end of each skidtube so that both bearpaw clamps are located aft of the aft saddle as shown in Figure 2 of IIN-D500-572 and Figure 32-1 of ICA-D500-572.
  - (ii) For the D500-572-021 Narrow Bearpaw Installation: Position D2671 Bearpaw on the aft end of each skidtube so that both bearpaw clamps are located aft of the aft saddle as shown in Figure 3 of IIN-D500-572 and Figure 32-2 of ICA-D500-572.
- 3.3 The bearpaw may be relieved to clear wearshoe mounting screws provided the relief leaves 0.375" (9.53mm) thickness.
- 3.4 For the D500-572-011 and D500-572-021 Bearpaw Installations, the QS200M44S Clamps must be installed behind the forward D5476-1 Clamp to ensure that the bearpaw doesn't slip, as shown in Figures 2 and 3 of IIN-D500-572 and Figures 32-1 and 32-2 of ICA-D500-572.
- 3.5 Attach the D5476-1 Clamps and D5472-1 Cushions with the hardware shown in Figure 1 of this Service Instruction. Additional NAS1149D0463J (or AN960J0416) washers may be installed under the nuts to ensure 1.5-4 threads in safety on the bolts. Although not generally necessary, it is also acceptable to replace the AN4-13A bolts with longer or shorter AN4 bolts, if required.

  CAUTION: The torque on the nuts should be limited to 20 in-lb (2.3 Nm)
- 3.6 Lower the aircraft.
- 3.7 Update the aircraft log book to indicate installation of the D500-572-011/-021 Bearpaw in compliance to DSI 9770.

#### 4.0 WEIGHT AND BALANCE

This DSI has a negligible effect on weight and balance. For installation of the D500-572-011/-021 Bearpaws on high gear, the weight and balance numbers provided in IIN-D500-572 Rev. A and ICA-D500-572 Rev. 0 are still applicable. For installation of the D500-572-011/-021 Bearpaws on low gear, the weight and balance numbers provided in DSI 9290 Rev. A are still applicable.

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED
D. SHEPHERD (DE # 02)

DATE: 17.01.09
CERT. NO.: SH90-17
ISSUE NO.: 7

	LVEWIO	0115		T	47.04.00	
Α	NEW ISSUE			MB	17.01.09	
REV.	DESCRIPTION			BY	DATE	
DESIGN	1	MB	DART AEROSPACE LTD			
DRAWN MB		MB	HAWKESBURY, ONTARIO, CANADA			
CHECKED ML		ML	DRAWING NO.		REV. A	
MFG. APPR. N/A		N/A	DSI 9770		SHEET 1 OF 3	
APPROVED HS ,		HS "	TITLE		SCALE	
DE APPR. DS-		DS-	CLAMP KIT		NTS	
DATE 17.01.09			COPYRIGHT © 2017 BY DA THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUP NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMM	PLIED ON THE EXPRE	SS CONDITION THAT IT IS	

NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

# **5.0 PARTS LIST**

The parts list for D500-572-011/-021 Bearpaw Kits are updated as follows:

Qty -011	Qty -021	Part Number	Description	
Х		D500-572-011	BEARPAW IN	NSTALLATION
	. X	D500-572-021	NARROW BE	ARPAW INSTALLATION
2		D2435	BEARPAW	
	2	D2671	BEARPAW	
<u> </u>			-	
8	8	D2274	RADIUS BLO	OCK
8	8	D2529	WASHER	
4	4	D5472-1	CUSHION	(REPLACES D2182B050)
4	4	D5476-1	CLAMP	(REPLACES D2438)
8	8	AN4-13A	BOLT	(WAS AN4-15A)
8	8	NAS1149D0463J	WASHER	(OR AN960JD416)
8	8	MS21042L4	NUT	(OR MS21042-4)
2	2	QS200M44S	CLAMP	

Operators who wish to upgrade their existing D500-572-011/-021 Bearpaw Kits in service can procure the DSI 9770-011 Clamp Kit from DART:

Qty -011	Part Number	Description	
X	DSI 9770-011	BEARPAW INSTALLATION	
8	D2274	RADIUS BLOCK	
8	D2529	WASHER	
4	D5472-1	CUSHION	
4	D5476-1	CLAMP	
8	AN4-13A	BOLT	
8	NAS1149D0463J	WASHER (OR AN960JD416)	
8	MS21042L4	NUT (OR MS21042-4)	
2	QS200M44S	CLAMP	

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01


BY: D. SHEPHERD (DE # 02)

DATE: CERT. NO.: ISSUE NO.:

17.01.09 SH90-17 7

	ŧ	
$\overline{}$		
<i>f</i> 1		
=	ı	
Ш		
ш	ľ	
_		
_		
		-
$\circ$	ı	
	E	
$\mathbf{C}$	ľ	
	ı	
_	ı	
<u> </u>	ı	
_	ı	
API	ı	
	ı	
~	ı	
~	ı	
	ı	
	ı	

DESIGN	MB	DART AEROSE	PACEITD
DRAWN	MB	HAWKESBURY, ONTARIO, CANADA	
CHECKED	ML	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9770	SHEET 2 OF 3
APPROVED	HS ,	TITLE	SCALE
DE APPR.	DS-	CLAMP KIT	NTS
DATE 17.01.09		COPYRIGHT © 2017 BY DA THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUP NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMM WRITTEN PERMISSION FROM DAR	PLIED ON THE EXPRESS CONDITION THAT IT IS UNICATED TO ANY OTHER PERSON WITHOUT



MS21042L4 NUT, SELF-LOCKING NAS1149D0463J WASHER D2274 RADIUS BLOCK D2529 WASHER AN4-13A BOLT 4 PL PER BEARPAW

FIGURE 1: SECTION VIEW (REPLACE SECTIONS A-A AND B-B OF IIN-D500-572 AND ICA-D500-572)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

BY: D. SHEPHERD (DE # 02)

DATE: CERT. NO.: ISSUE NO.: 17.01.09 SH90-17 7

Ĺ	_	1	
Ĺ	1	J	
`	>	>	
Ć	_	)	
Č	ī	-	
Ē	١	_	
Ē	ì	_	
<	1	٥	
		-	

DESIGN	MB	
DRAWN	MB	
CHECKED	ML	
MFG. APPR.	N/A	
APPROVED	HS	
DE APPR.	DS	
DATE 17.01.09		

DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA			
DSI 9770	REV. A SHEET 3 OF :		
TITLE CLAMP KIT	SCALE		

COPYRIGHT © 2017 BY DART AEROSPACE LTD.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.